

REMOVAL/INSTALL OF CONSOLE LID (924-877) Dodge Ram 2002-05

General Tech Tip:

- A plastic pry tool is useful. It will not easily damage delicate trim like a screwdriver or metal pry bar.

**PLEASE WEAR
SAFETY GLASSES!**

Tool required for removal and installation of console lid:

- **Phillips screwdriver or power screwdriver with Phillips attachment**



Removal Instructions

STEP 1: Lift the console lid to the up position.



STEP 2: Using a Phillips screwdriver or power screwdriver with Phillips attachment, remove the four (4) screws on the bottom of the console lid.



STEP 3: Remove the console lid from the center console.

INSTALL/REMOVAL INSTRUCTIONS: CONSOLE LID


ATTENTION: Refer to the appropriate shop manual for your vehicle to obtain specific service procedures for this part. If you do not have a service manual or lack the skill to install this part, it is recommended that you seek the services of a qualified technician. Pay special attention to all cautions and warnings included in the shop manual. Read and follow all instructions carefully.

Installation Instructions

STEP 1: Place the new console lid on the center console, making sure to line up the holes for the screws.



STEP 2: Using a Phillips screwdriver or power screwdriver with Phillips attachment, attach the four (4) screws on the bottom of the console lid.



STEP 3: Verify that all of the hardware is secure and close the console lid to ensure that it latches properly.